

# SPECIFICATION SHEET

Glove Style: 0921/10

Description: Yellow, 100% Nitrile fully coated interlock cotton liner for comfort with knitted wrist. Designed for durability & high dexterity.

(0.7mm ± 0.0 mm thickness)

Series:  
0921 Fully Coated - Knitted Wrist

Sizes Available:

SIZE AS PER EN 420	MARKED SIZE
10	Large
*Indicates fit for special purpose Glove measured when laid flat and relaxed	

### Cleaning & Maintenance:

Gloves should not be left in contaminated condition if re-use is intended especially if potential hazards exist. Before removal from the hands excess contaminant should first be removed however, should this not be possible, it is advisable to ease left and right hand gloves off using the gloved hand & remove the gloves without the contaminant contacting the bare hands. The gloves may then be decontaminated with mild detergent solution, then rinsed with clean water and dried ideally with some air movement. All gloves should be thoroughly inspected before use to ensure no damage is present.

### Storage:

Store the gloves the original packaging in a cool dry place and out of direct sunlight.

### Packaging:

The standard packaging for the gloves are as follows. The gloves are not packed in individual bags "inbg". The gloves are packed in bundles in a polybag "plbg". The "plbg" glove bundles are placed in cardboard cartons "ctn" suitable for transportation and storage.

### Obsolescence:

Stored correctly, the gloves physical properties will not change for up to three years.

### General:

None of the materials or processes used in the manufacture of these products is known to be harmful to the wearer. The manufacturer has examined under the system for ensuring quality of production by means of monitoring and inspection. The gloves are designed to accommodate the basic safety requirements and standards for Personal Protective Equipment. The information contained herein is intended to assist the wearer in the selection of personal protective equipment. Actual conditions of use cannot be directly simulated in a test environment so it is therefore the responsibility of the end user and not the manufacturer or supplier to determine the gloves suitability for the intended use.

CTC.fr

**0921**

**YELLOW NITRILE**



INTERMEDIATE DESIGN

MARKING

**Dromex**



EN 388



CE

0075



4111

**0921  
SIZE 10**

Tested in accordance with the European directive for PPE (89/686/EEC) for intermediate design, and is tested to EN 388.

www.dromex.net

File: dromex-spec-0921.doc



0921

**CE** EN 388:1994  
MECHANICAL RISKS



A ABRASION RESISTANCE  
Number of cycles (6.1)

1	2	3	4	5
100	500	<b>2000</b>	8000	~

B BLADE CUT RESISTANCE  
Index (6.2)

1	2	3	4	5
<b>1,2</b>	2,5	5,0	10,0	20,0

C TEAR RESISTANCE  
Newton's (6.3)

1	2	3	4	5
<b>10</b>	25	50	75	~

D PUNCTURE RESISTANCE  
Newton's (6.4)

1	2	3	4	5
<b>20</b>	60	100	150	~