

Description:

Dromex® Mechanics Gloves with impact-absorbing & Three-Dimensional Protection for Palm , Finger , Knuckle and back of hand, with water-resistance liner inside, 15cm length of Neoprene cuff for water proof and special protection for added wrist and forearm. .

This multi-functional mechanical glove features not only finger and thumb protection, but also knuckle and back of hand protection, with the maximum dexterity and non-slip performance, specially the water resistance liner inside. The yellow TPR ribs run all way to the fingertips and to the end of the thumb. The soft TPR ribs can absorb the energy froe blow and direct it along the length of the glove, reducing the risk of serious injury. It designed to provide optimum balance between flexibility and impact dispersion. Synthetic leather palm and Impregnated PVC dots adhere to the palm of the glove to enhance overall grip. Raised PVC dots extend the life of the glove by absorbing wear away from the palm fabric. Neoprene cuff provides added wrist and forearm protection.

Especially designed for the oil and gas industries and multiple protection for any industry , this high visible glove is the ideal safety glove for numerous industries as oil and gas, mining, automotive, assembling, packaging, warehousing both indoor and outdoor.

Sizes Available:

SIZE AVAILABLE	8'-M, 9'-L, 10'-XL
----------------	--------------------

Cleaning & Maintenance:

Gloves should not be left in contaminated condition if re-use is intended especially if potential hazards exist. Before removal from the hands excess contaminant should first be removed however, should this not be possible, it is advisable to ease left and right hand gloves off using the gloved hand & remove the gloves without the contaminant contacting the bare hands. The gloves may then be de-contaminated as indicated below:



Dromex® mechanical gloves have proven that dry cleaning as well as laundering are suitable cleaning methods.

We recommend that no bleaching or oxidising ingredients or any fabric softeners be used.

Recommended washing temperature is between 40°C and 60°C (104~140°F) with mild detergents.

The drying process may cause felting on the fabric surface. Drying temperature should not exceed 60°C (140°F).

There is no remarkable impact on cut resistance and anti-impact during the normal life cycle of a glove however, depending on glove construction, staining and cleaning method, the differences in shrinkage, weight loss, yarn strength and colour may occur. In order to maximise the glove life cycle we recommend the mildest possible cleaning conditions in terms of temperature, chemicals and cycle duration.



Due to a wide variety of possible constructions and combinations with other materials we recommend to always consult your professional cleaning service to determine the best suitable cleaning method.

Storage:

Store the gloves the original packaging in a cool dry place and out of direct sunlight and UV light.

Packaging:

The gloves are packed in individual bags. The gloves are placed in cardboard cartons suitable for transportation and storage.

Obsolescence:

Stored correctly, the gloves physical properties will not change for up to three years.

None of the materials or processes used in the manufacture of these products is known to be harmful to the wearer. The manufacturer has examined under the system for ensuring quality of production by means of monitoring and inspection. The gloves are designed to accommodate the basic safety requirements and standards for Personal Protective Equipment. The information contained herein is intended to assist the wearer in the selection of personal protective equipment. Actual conditions of use cannot be directly simulated in a test environment so it is therefore the responsibility of the end user and not the manufacturer or supplier to determine the gloves suitability for the intended use.

All gloves should be thoroughly inspected before use to ensure no damage is present.



MACH 2WP15 MECHANICAL GLOVE



Tested in accordance with the European directive for PPE (89/686/EEC) for simple design, and is compliant with EN 420, EN 388.

www.dromex.net



CE EN 388:1994
MECHANICAL RISKS

A ABRASION RESISTANCE
Number of cycles (6.1)

1	2	3	4	5
100	500	2000	8000	~

B BLADE CUT RESISTANCE
Index (6.2)

1	2	3	4	5
1,2	2,5	5,0	10,0	20,0

C TEAR RESISTANCE
Newton's (6.3)

1	2	3	4	5
10	25	50	75	~

D PUNCTURE RESISTANCE
Newton's (6.4)

1	2	3	4	5
20	60	100	150	~

3-D MULTI-PROTECTION FOR HAND

LINT FREE

WASHABLE

DROMEX® mechanical glove is a high performance innovative product engineered from the experts from Oil and gas Industry from USA and developed specifically for Hand Protection. This 3-Dimensional protective glove with Hi-visible TPR ribs for Anti-impact is both comfortable and flexible, the water resistance liner provides the special function. Designed to address a multitude of applications and reduce the Three biggest hand injuries; Hairline Fractures, Bruising Blows and Pinched Fingers.

The heavy duty rubber ribs are designed to absorb and dissipate impacts to the back of the hand.

TPR padding for impact-absorbing for Finger and Knuckle placed between fabric layers provides added protection and flexibility.

Water-resistance liner inside, 15cm length of Neoprene cuff for water proof and special protection for added wrist and forearm.

TYPICAL USES

OIL AND GAS INDUSTRY

AUTOMOTIVE / AEROSPACE

LOGISTIC AND PROCESS

PACKAGING / ASSEMBLING

GENERAL MAINTENANCE