

# SPECIFICATION SHEET

Glove Style: **GTIG**

Description: Pigskin grain leather TIG welders or drivers glove. Tan dyed pigskin premium grain leather gunn cut, keystone thumb, shirred, sewn with syntax thread. Cotton bound cuff.

Series:  
GTIG Cotton (Red) bound cuff.

Sizes Available:

SIZE AS PER EN 420
8
9
10
11
12
*Indicates fit for special purpose Glove measured when laid flat and relaxed

## Cleaning & Maintenance:

Both new and used gloves should be thoroughly inspected before use to ensure no damage is present. Gloves should not be left in contaminated state if re-use is intended, more especially if a potential hazard exists. Before removal from the hands excess contaminant should first be removed however if this is not possible the gloves should be removed without the contaminant contacting the bare hands. The gloves may then be de-contaminated with mild detergent solution and then wiped clean with a damp cloth and dried ideally with some air movement. As this product is constructed with natural leather, hazardous contaminants might be retained in the leather.

## Storage:

Store the gloves the original packaging in a cool dry place and out of direct sunlight.

## Packaging:

The standard packaging for the gloves are as follows. The gloves are not packed in individual bags "inbg". The gloves are packed in bundles in a polybag "plbg". The "plbg" glove bundles are placed in cardboard cartons "ctn" suitable for transportation and storage.

## Obsolescence:

Stored correctly, the gloves physical properties will not change for up to three years.

## General:

None of the materials or processes used in the manufacture of these products is known to be harmful to the wearer. The manufacturer has examined under the system for ensuring quality of production by means of monitoring and inspection. The gloves are designed to accommodate the basic safety requirements and standards for Personal Protective Equipment. The information contained herein is intended to assist the wearer in the selection of personal protective equipment. Actual conditions of use cannot be directly simulated in a test environment so it is therefore the responsibility of the end user and not the manufacturer or supplier to determine the gloves suitability for the intended use.

## Innoxiousness:

These gloves have been tested to EN 420 pH levels comply with section 4.4.2 Chromium VI levels comply with section 4.4.3

## Note:

Leather, a natural product, varies between hides due to thickness, scare tissue, etc. The minimum specified tolerance for the leather is designed to achieve these desired specifications.

# GTIG

PIG GRAIN LEATHER TIG WELDER



INTERMEDIATE  
DESIGN

MARKING

**Dromex**



**GTIG**

EN 388



4122

**SIZE 10**

Tested in accordance with the European directive for PPE (89/686/EEC) for intermediate design, and is tested to EN 388.

**DROMEX**

www.dromex.net

File: dromex-spec-gtig.doc



# GTIG

**CE** EN 388:1994  
MECHANICAL RISKS



**A** ABRASION RESISTANCE  
Number of cycles (6.1)

1	2	3	4	5
100	500	2000	<b>8000</b>	~

**B** BLADE CUT RESISTANCE  
Index (6.2)

1	2	3	4	5
<b>1,2</b>	2,5	5,0	10,0	20,0

**C** TEAR RESISTANCE  
Newton's (6.3)

1	2	3	4	5
10	<b>25</b>	50	75	~

**D** PUNCTURE RESISTANCE  
Newton's (6.4)

1	2	3	4	5
20	<b>60</b>	100	150	~